

Entalloy B Torch **Repair, Rebuild and Protect**

Metal Parts and Implements





 Triple the life of metal parts and implements to extend part life almost indefinitely.

 "Low Heat Input" process minimizes distortion of the base metal and allows thin selections to be coated.

- Deposits can be precisely applied with a high degree of welder control.
- Offers a practical solution to a wide range of wear problems.
- Rugged, reliable and user friendly!





PRODUCT INFORMATION

Outstanding Features:

1) Unlimited Versatility: Provides capability of deposits from 0.002" to 1/4"in one pass!

2) *Incomparable Precision:* Operator puts exact amount of alloy where he/she wants it.

3) Unmatched Capability: Designed for use on iron, nickel, stainless steel, cobalt and selected copper base metals.

4) *Maximum Utility:* The essence of simplicity, no special skill required!

5) Superior Craftsmanship: Precision-designed for the craftsman, for the professional welder and maintenance man who appreciates a quality tool.

6) *Maintenance Free:* Fully chrome plated over durable, rugged torch body assures trouble-free productive operation.

7) *Super Safety:* Built-In UL approved "Flo-Safe" reverse flow check valves to prevent any danger of backflow.

Additional Features:

A) Forward assembly permits 360° rotation of the tip for convenient work in any position.

B) Removable heat shield protects hands during extended work....it also serves as a stand when not in use.

The System:

The key to the Eutalloy system is based on the integrated function of two components: 1) the special self-fluxing Eutalloy powders that are designed for virtually all base metals and 2) the simplicity and accuracy of the Eutalloy torch.

The Eutalloy torch is a quality tool designed to be used with standard oxy-acetylene gas equipment. The heart of the torch is a precision gas and powder mixing chamber which introduces the powdered metal alloys into the gas stream and through the flame where they are deposited and molted on the base metal.

The operator has complete control over the deposit size and shape by simply depressing or releasing the feed lever.

Eutectic Corporation Your Resource For Protection, Repair And Joining Solutions



Eutectic Corporation

N94 W14355 Garwin Mace Drive Menomonee Falls, WI 53051 USA P 800-558-8524 • F 262-255-5542 www.eutecticusa.com Eutectic Canada 428, rue Aime Vincent Vaudreuil-Dorion, Quebec J7V 5V5 Phone: (800) 361-9439 Fax: (514) 695-8793

Eutectic Mexico

KM 36.5 Autopista Mexico-Quertaro 54730 Cautitlan-Izcalli Estado de Mexico, Mexico Phone: 011(52) 55-5872-1111 e-mail: eutectic.mexico@eutectic.com.mx

Statement of Liability: Due to variations inherent in specific applications, the technical information contained herein, including any information as to suggested product applications or results, is presented without representation or warranty, expressed or implied. Without limitation, there are no warranties of merchantability or of fitness for a particular purpose. Each process and application must be fully evaluated by the user in all respects, including suitability, compliance with applicable law and non-infringement of the rights of others, and Eutectic Corporation and its affiliates shall have no liability in respect thereof. EUTBDS-07-21-09